



GT-2418

8 digital outputs

24 VDC / 0.5 A

Transistor SINK

Diagnostics

Short circuit protection

Over current limit & Thermal shutdown

18pt removable terminal block

Facts

General description

| | |
|------------------------|---|
| Article number | 100-8128 |
| Warranty | Up to 2 years |
| Article status | Active |
| Shock operating | IEC 60068-2-27 (15G) |
| Vibration resistance | Sine vibration (based on IEC 60068-2-6), 5 ~ 25 Hz: $\pm 1.6\text{mm}$, 25 ~ 300 Hz: 4G, Sweep rate: 1 octave/min., 20 cycles, Random vibration (based on IEC 60068-2-64), 10 ~ 40 Hz: $0.0125\text{g}^2/\text{Hz}$, 40 ~ 100 Hz: $0.0125 \rightarrow 0.002\text{g}^2/\text{Hz}$, 100 ~ 500 Hz: $0.002 \text{g}^2/\text{Hz}$, 500 ~ 2000 Hz: $0.002 \rightarrow 1.3 \times 10^{-4}\text{g}^2/\text{Hz}$, Test time: 1hrs for each test |
| Industrial emissions | EN 61000-6-4/A11: 2011 |
| Industrial immunity | EN 61000-6-2: 2019 |
| Product certifications | Horisontal, Vertical CE, UL, cUL, FCC, RoHS, China RoHS, Reach |
| Power dissipation | Max. 55 mA @ 5 VDC |
| Isolation | I/O to Logic: Photocoupler isolation, I/O to Field Power: Non-Isolation |
| Field power | Nominal supply voltage: 24 VDC, Voltage range: 60°C: 18~32 VDC, 70°C: 18~26.4 VDC |
| Weight | 65 g |
| Module size | 12x109x70 mm |

Environmental

| | |
|-----------------------|------------------------|
| Mounting | 35mm DIN rail |
| Operating temperature | -20 ~ 60°C |
| Storage temperature | -40 ~ 85°C |
| UL temperature | -20 ~ 60°C |
| Relative humidity | 5 ~ 90% non-condensing |

Digital output module specifications

| | |
|---------------------------|--|
| Indicators | 8 green output status |
| Outputs per module | 8 point SINK |
| Output current rating | Max. 0.5 A per channel, Max. 4 A per unit |
| Output signal delay | OFF to ON: Max. 0.3 ms, ON to OFF: Max. 0.4 ms |
| ON state min current | Min. 1 mA |
| Output voltage range | Nominal supply voltage: 24 VDC, Voltage range: 60°C: 18~32 VDC, 70°C: 18~26.4 VDC |
| ON state voltage | Max. 0.3 VDC @ 25°C, , Max. 0.5 VDC @ 60°C |
| OFF state leakage current | Max. 20 uA |
| Common type | 8 point / 2 COM |
| Protection | Over current limit: 3.5 A@ 25°C per channel, Thermal Shutdown: 175°C, Short circuit protection |

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Beijer Electronics, Inc.
850 South 3600 West, Suite C
Salt Lake City, UT 84104
USA

Sales: +1 801-708-6631 Support: +1 801-708-6690 (tel:Sales: +1 801-708-6631 Support: +1 801-708-6690)
sales.americas@beijerelectronics.com (mailto:sales.americas@beijerelectronics.com)