



GT-2618

8 digital outputs

24 VDC, max. 2 A / channel

Transistor SINK

10pt removable terminal block

Facts

General description

Article number	100-8007
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), 5 ~ 25 Hz: $\pm 1.6\text{mm}$, 25 ~ 300 Hz: 4G, Sweep rate: 1 octave/min., 20 cycles, Random vibration (based on IEC 60068-2-64), 10 ~ 40 Hz: $0.0125\text{g}^2/\text{Hz}$, 40 ~ 100 Hz: $0.0125 \rightarrow 0.002\text{g}^2/\text{Hz}$, 100 ~ 500 Hz: $0.002 \text{g}^2/\text{Hz}$, 500 ~ 2000 Hz: $0.002 \rightarrow 1.3 \times 10^{-4}\text{g}^2/\text{Hz}$, Test time: 1hrs for each test
Industrial emissions	EN 61000-6-4/A11: 2011
Industrial immunity	EN 61000-6-2: 2019
Product certifications	Horisontal, Vertical CE, UL, cUL, FCC, RoHS, China RoHS, Reach
Power dissipation	Max. 50 mA @ 5 VDC
Isolation	I/O to Logic: Photocoupler isolation, I/O to Field Power: Non-Isolation
Field power	Nominal supply voltage: 24 VDC, Voltage range: 60°C: 18~32 VDC, 70°C: 18~26.4 VDC
Weight	70 g
Module size	12x99x70 mm

Environmental

Mounting	35mm DIN rail
Operating temperature	-20 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-20 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

Digital output module specifications

Indicators	8 green output status
Outputs per module	8 point SINK
Output current rating	Max. 2 A per channel, Operating temperature -40°C~50°C : Max. 10 A per unit 50°C~60°C : Max. 7 A per unit 60°C~70°C : Max. 4.8 A per unit
Output signal delay	OFF to ON: Max. 0.3 ms, ON to OFF: Max. 0.3 ms
ON state min current	Min. 1 mA
Output voltage range	Nominal supply voltage: 24 VDC, Voltage range: 15~30 VDC
ON state voltage	Max. 1 VDC @ 25°C
OFF state leakage current	Max. 5 uA
Common type	8 point / 2 COM

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Beijer Electronics, Inc.
850 South 3600 West, Suite C
Salt Lake City, UT 84104
USA

Sales: +1 801-708-6631 Support: +1 801-708-6690 (tel:Sales: +1 801-708-6631 Support: +1 801-708-6690)
sales.americas@bejerelectronics.com (mailto:sales.americas@bejerelectronics.com)