



GT-3708

8 channels RTD

3-wire RTD input

PT100 / PT1000 / Ni1000LG / etc,

20-pin connector (cable not included)

Con20-Open-Cab 5m can be used in combination (part.no. 313296)

Facts

General description

Article number	100-8041
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), 5 ~ 25 Hz: $\pm 1.6\text{mm}$, 25 ~ 300 Hz: 4G, Sweep rate: 1 octave/min., 20 cycles, Random vibration (based on IEC 60068-2-64), 10 ~ 40 Hz: $0.0125\text{g}^2/\text{Hz}$, 40 ~ 100 Hz: $0.0125 \rightarrow 0.002\text{g}^2/\text{Hz}$, 100 ~ 500 Hz: $0.002 \text{g}^2/\text{Hz}$, 500 ~ 2000 Hz: $0.002 \rightarrow 1.3 \times 10^{-4}\text{g}^2/\text{Hz}$, Test time: 1hrs for each test
Industrial emissions	EN 61000-6-4/A11: 2011
Industrial immunity	EN 61000-6-2: 2019
Product certifications	Horizontal, Vertical CE, UL, cUL, FCC, RoHS, China RoHS, Reach
Power dissipation	Max. 135 mA @ 5 VDC
Isolation	I/O to Logic: Photocoupler isolation, I/O to Field Power: Non-Isolation
Field power	Not used. Field power bypassed to next expansion module.
Weight	60 g
Module size	12x99x70 mm

Environmental

Mounting	35mm DIN rail
Operating temperature	-20 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-20 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

Analog input module specifications

Calibration	Not required
Connection types	3-Wire
Conversion time	≤ 280 ms, all channels
Data format	16 bit integer (2's complement)
Excitation current	About 1 mA
Indicators	8 green input status
Inputs per module	8 channel
Module accuracy	PT100, PT1000, ±0.5% full scale @ 25°C ambient, , All other type, ±0.1% full scale @ 25°C ambient, ±0.3% full scale @ -40°C, 70°C
Resolution in ranges	RTD Type: ±0.1°C/ F , Resistance type: 100 / 10 / 20 / 50 mΩ
Sensor types	RTD Input, , PPT1000 (PT1000 Precise Mode): 50~150°C, Cu10,Cu100: 100~260°C, PT100, PT200, PT500, PT50: 200~850°C, PT1000: 200~350°C, JPT100, JPT200, JPT500, JPT50: -200~640°C, JPT1000: -200~350°C, NI100, NI200, NI500: -60~250°C, NI1000: -60~180°C, NI120: -80~260°C, NI1000LG: -50~120°C, , Resistance Input, , 100mΩ/bit: 0~2000Ω, 10mΩ/bit: 0~327Ω, 20mΩ/bit: 0~620Ω, 50mΩ/bit: 0~1200Ω

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Beijer Electronics, Inc.
850 South 3600 West, Suite C
Salt Lake City, UT 84104
USA

[Sales: +1 801-708-6631](tel:+18017086631) [Support: +1 801-708-6690](tel:+18017086690) (tel:[Sales: +1 801-708-6631](tel:+18017086631) [Support: +1 801-708-6690](tel:+18017086690))
sales.americas@beijerelectronics.com (mailto:sales.americas@beijerelectronics.com)