



GT-5122

High speed counter

2 channels

Encoder voltage: 5~24 VDC

Up to 750 kHz

Gate Function Mode (position catch)

18pt removable terminal block

Facts

General description

Article number	100-8098
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), 5 ~ 25 Hz: $\pm 1.6\text{mm}$, 25 ~ 300 Hz: 4G, Sweep rate: 1 octave/min., 20 cycles, Random vibration (based on IEC 60068-2-64), 10 ~ 40 Hz: $0.0125\text{g}^2/\text{Hz}$, 40 ~ 100 Hz: $0.0125 \rightarrow 0.002\text{g}^2/\text{Hz}$, 100 ~ 500 Hz: $0.002 \text{g}^2/\text{Hz}$, 500 ~ 2000 Hz: $0.002 \rightarrow 1.3 \times 10^{-4}\text{g}^2/\text{Hz}$, Test time: 1hrs for each test
Industrial emissions	EN 61000-6-4/A11: 2011
Industrial immunity	EN 61000-6-2: 2019
Product certifications	Horisontal, Vertical CE, UL, cUL, FCC, RoHS, China RoHS, Reach
Power dissipation	Max. 120 mA @ 5 VDC
Isolation	I/O to Logic: Photocoupler isolation, I/O to Field Power: Non-Isolation
Field power	Nominal supply voltage: 24 VDC, Voltage range: 60°C: 18~32 VDC, 70°C: 18~26.4 VDC
Weight	60 g
Module size	12x99x70 mm

Environmental

Mounting	35mm DIN rail
Operating temperature	-20 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-20 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

Communication module specification

Transfer channels	2 Channel, Encoder, High Speed Counter, Frequency measurement Pulse width & Period measurement
-------------------	--

Counter mode specifications

Counter size	32bit-wide/channel
Counting mode	1-Input Mode: Up, Down, 2-Input Mode: Encoder 4x, Up/Inhibit, Up/Reset, Down/Inhibit, Down/Reset, UP/Down, Clock/Direction,, Frequency Measurement,, Pulse Width & Period measurement, , Gate function mode: Store/Continue, Store/Wait/Resume, Store-Reset/Wait/Start, Store-Reset/Start, , Digital IO with 0.3 ms response delay: 2 digital inputs (24 VDC, sink), 2 digital outputs (24 VDC, source, max 0.3 A)
Indicators	6 Green Terminal Input LEDs
Input current	5 mA @ 5 VDC, 12 mA @ 24 VDC
Input frequency	0~500 kHz Count Mode, 0~750 kHz Encoder Mode
Input voltage	5~24 VDC
Min ON state voltage	≥3.5 VDC
Number of channels	2 Channel, Encoder, High Speed Counter, Frequency measurement Pulse width & Period measurement

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Beijer Electronics, Inc.
850 South 3600 West, Suite C
Salt Lake City, UT 84104
USA

Sales: +1 801-708-6631 Support: +1 801-708-6690 (tel:Sales: +1 801-708-6631 Support: +1 801-708-6690)
sales.americas@beijerelectronics.com (mailto:sales.americas@beijerelectronics.com)