




M2628

8 digital outputs

24 VDC (2 A)

Transistor SOURCE

Hotswap

18pt removable terminal block (RTB18C)

Facts

General description

Article number	100-8220
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), DNVGL-CG-0339 (Vibration Class B, 4G)
Industrial emissions	EN 61000-6-4/2019
Industrial immunity	EN 61000-6-2 : 2019
Power dissipation	Horizontal, Vertical 40 mA maximum @ 5.0 VDC
Isolation	I/O to Logic : Photocoupler isolation
Field power	Supply voltage : 24 VDC nominal, Voltage range : 15~28.8 VDC, Power dissipation: 40 mA maximum @ 28.8 VDC
Weight	72g
Module size	12 x 110 x 75 mm

Certifications

General	CE, FCC, UL, cUL
Hazardous	UL C1D2, ATEX (Zone2)
Marine	DNV GL
Safety	UL508, CAN/CSA C22.2 No.142-M1987

Environmental

Mounting	35mm DIN rail
Operating temperature	-25 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-25 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

Digital output module specifications

Indicators	8 Green output state
Outputs per module	8 channels Source type
Output current rating	Max. 2A per channel, Operating Temperature: -25°C~50°C : Max. 10A per unit, 50°C~55°C : Max. 7A per unit
Output signal delay	OFF to ON : 0.3mS maximum, ON to OFF : 0.5mS maximum
ON state min current	1mA per channel
Output voltage range	Nominal 24 VDC, Min. 15 VDC ~ Max. 28.8 VDC
ON state voltage	Max. 1.0 VDC @ 25°C
OFF state leakage current	Max. 5 uA
Common type	8 channels / 8COM (Single Common)

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Beijer Electronics, Inc.
850 South 3600 West, Suite C
Salt Lake City, UT 84104
USA

Sales: +1 801-708-6631 Support: +1 801-708-6690 (tel:Sales: +1 801-708-6631 Support: +1 801-708-6690)

sales.americas@bejerelectronics.com (mailto:sales.americas@bejerelectronics.com)