



## M347F

16 analog inputs

0~10/0~5/1~5VDC

12 bit resolution

Hotswap

18pt removable terminal block (RTB18C)

## Facts

### General description

Article number	100-8233
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), DNVGL-CG-0339 (Vibration Class B, 4G)
Industrial emissions	EN 61000-6-4/2019
Industrial immunity	EN 61000-6-2 : 2019
Installation position	Horisontal, Vertical
Power dissipation	Max. 200 mA @ 5.0 VDC
Isolation	I/O to Logic : DC-DC Isolation, Field power : Not Connected
Field power	Not used Field power bypass to next expansion module
Weight	72g
Module size	12 x 110 x 75 mm

## Certifications

General	CE, FCC, UL, cUL
Hazardous	UL C1D2, ATEX (Zone2)
Marine	DNV GL
Safety	UL508, CAN/CSA C22.2 No.142-M1987

## Environmental

Mounting	35mm DIN rail
Operating temperature	-25 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-25 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

## Analog input module specifications

Calibration	Not required
Common type	2 Common
Conversion time	All Channel<1.3 ms, Field calibration
Data format	16 bits Integer (2 <sup>1</sup> compliment)
Diagnostic	Sensor open or range over, then conversion data = 0x8000(-32768)
Indicators	1 Green M-Bus status LED
Input current range	0~10 VDC, 0~5 VDC, 1~5 VDC
Input impedance	500 kΩ
Inputs per module	16 Channels single ended, non-isolated between channels
Module error	±0.1% Full Scale @ 25°C ambient, ±0.3% Full Scale @ -25°C~60°C
Resolution in ranges	12 bits : 2.44 mV/Bit (0~10 V) , 1.22 mV/Bit (0~5 V), 0.98 mV/Bit (1~5 V)

## People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmö, SWEDEN

[+46 40 35 86 00](tel:+4640358600) (tel:+46 40 35 86 00)

[info@bejerelectronics.com](mailto:info@bejerelectronics.com) (mailto:info@bejerelectronics.com)

