




M4158

8 analog outputs

0~20 mA

16 bit resolution

Hotswap

18pt removable terminal block (RTB18C)

Facts

General description

Article number	100-8246
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), DNVGL-CG-0339 (Vibration Class B, 4G)
Industrial emissions	EN 61000-6-4/2019
Industrial immunity	EN 61000-6-2 : 2019
Installation position	Horisontal, Vertical
Power dissipation	Max. 30 mA @ 5.0 VDC
Isolation	I/O to Logic : Photocoupler Isolation, Field power : Non-Isolation
Field power	Supply voltage : 24 VDC Norminal Voltage range : 18V ~ 28.8 VDC Power dissipation : 130 mA @ 24 VDC
Weight	72g
Module size	12 x 110 x 75 mm

Certifications

General	CE, FCC, UL, cUL
Hazardous	UL C1D2, ATEX (Zone2)
Marine	DNV GL
Safety	UL508, CAN/CSA C22.2 No.142-M1987

Environmental

Mounting	35mm DIN rail
Operating temperature	-25 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-25 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

Analog output module specifications

Calibration	Not Required
Common type	8 Common, Field Power 0V is Common(AGND)
Conversion time	Max. 250usec / All channel
Data format	16 bits Integer (2' compliment)
Diagnostics	Field Power Off : Led Blinking, Field Power On : Led ON
Indicators	1 Green M-Bus status
Load resistance	<200 Ω
Module error	$\pm 0.1\%$ Full Scale @ 25°C ambient, $\pm 0.3\%$ Full Scale @ -25°C~60°C
Output format	0~20 mA
Outputs per module	8 Channels single ended
Resolution in ranges	16 bit (Include Sign), 15 bits : 0.61 uA/bit

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software, hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Visiting address HQ: Stora Varvsgatan 13a

SE - 211 75 Malmoe, SWEDEN

[+46 40 35 86 00](tel:+4640358600) (tel:+46 40 35 86 00)

info@beijerelectronics.com (mailto:info@beijerelectronics.com)

