




M9273

Network adapter

Modbus RTU adapter

128 bytes (input + output)

Up to 63 expansion slices

M7001 power module

18pt removable terminal block (RTB18C)

Facts

General description

Article number	100-8205
Warranty	Up to 2 years
Article status	Active
Shock operating	IEC 60068-2-27 (15G)
Vibration resistance	Sine vibration (based on IEC 60068-2-6), DNVGL-CG-0339 (Vibration Class B, 4G)
Industrial emissions	EN 61000-6-4/2019
Industrial immunity	EN 61000-6-2 : 2019
	Horizontal, Vertical
System power	UL System Power: Supply voltage : 24 VDC nominal, Class 2 System Power, Supply voltage : Class 2, 24 VDC nominal, Supply voltage range : 15~28.8 VDC, Protection : Output current limit / Reverse polarity protection
Power dissipation	70 mA typical @ 24 VDC
Current for IO module	2.0A @ 5 VDC (If except for NA, current for I/O module is about 1.7A)
Isolation	System power to internal logic : Non-isolation, System power I/O driver : Isolation
Field power	Supply voltage : 24 VDC typical (Max.28.8 VDC), * Field Power Range is different depending on IO Module series. Refer to IO Module's Specification.
Max current field power contact	DC 10A Max
Weight	179g
Module size	54 x 110 x 75 mm

Certifications

General	CE, FCC, UL, cUL
Hazardous	UL C1D2, ATEX (Zone2)
Marine	DNV GL
Safety	UL508, CAN/CSA C22.2 No.142-M1987

Communication

Redundancy	No
Station type	Slave
IO data size	128 bytes (input + output)
Max length bus line	1200 m
Max network nodes	99 nodes
Baud rate	2400, 4800, 9600, 19200, 38400, 57600, 115200 bps
Bus connection	5 Pin Open-Style Connector
Other serial port	RS232 for MODBUS RTU (Touch Panel or IOGuide)
Serial configuration	Node: 1 (Fixed), Baud Rate: 115200 (Fixed), Data bit: 8 (Fixed), Parity bit: No parity (Fixed), Stop bit: 1 (Fixed)
Indicator	4 LEDs: 1 Green/Red, Module Status (MOD), 1 Green, Receive Data (RXD), 1 Green, Transmit Data (TXD), 1 Green/Red, Expansion I/O Module Status (IOS)
Module location	Starter module left side
Field power detection	~14 VDC

Environmental

Mounting	35mm DIN rail
Operating temperature	-25 ~ 60°C
Storage temperature	-40 ~ 85°C
UL temperature	-25 ~ 60°C
Relative humidity	5 ~ 90% non-condensing

Power module specifications

	DC 10A Max
Field power voltage	24VDC
Indicator	M7001: 4 LEDs: 1 Green, M-Bus Status (RUN), 1 Green, Primary Status(PRI), 1 Green, Active Status (ACT), 1 Green, Field Power Enable (Field Power)
Input voltage range	15 VDC to 28.8 VDC
Power input voltage	24VDC

People & Technology. Connected.

We are a people company. Our experienced, skilled and passionate people empower you to meet your challenges through best-in-class, user-friendly solutions. We are a technology company. We help you optimize processes through our software,

hardware and services, and through our support. Connecting people and technologies gives you the means to accomplish your goals and ambitions, and gain a competitive edge in today's digitalized world.

Beijer Electronics, Inc.
850 South 3600 West, Suite C
Salt Lake City, UT 84104
USA

Sales: +1 801-708-6631 Support: +1 801-708-6690 (tel:Sales: +1 801-708-6631 Support: +1 801-708-6690)
sales.americas@beijerelectronics.com (mailto:sales.americas@beijerelectronics.com)